



YOUR EVERYDAY PERFORMANCE

TMDROUTH H 3500

Product	TMNM2T-TH3500	TMNM2T-TH3500	TMNM2T-TH3500	TMNM2T-TH3500	TMNM2T-TH3500
Capacity	500GB	1TB	2TB	4TB	8TB
UPC	850028113332	850028113349	850028113356	850028113363	850028113370
Nand	3D TLC NAND				
Controller	Silicon Motion SM2262EN		Phison E12S		
Interface	PCIe Gen3 x4 NVMe 1.3				
Monitoring	S.M.A.R.T, TRIM, NVME secure erase				
Certifications	FCC, CE, RoHS				
Sequential Read	Up to 3500MB/s	Up to 3500MB/s	Up to 3500MB/s	Up to 3200MB/s	Up to 3400MB/s
Sequential Write	Up to 2300MB/s	Up to 3000MB/s	Up to 3100MB/s	Up to 3000MB/s	Up to 3000MB/s
Random 4K Read	Up to 344,000	Up to 331,000	Up to 339,000	Up to 550,000 IOPS	Up to 550,000 IOPS
Random 4K Write	Up to 343,000	Up to 353,000	Up to 358,000	Up to 640,000 IOPS	Up to 640,000 IOPS
Power Consumption	Up to 0.3W (Idle) 5.3W(Active)	Up to 0.3W (Idle) 5.7W(Active)	Up to 0.3W (Idle) 5.7W(Active)	Up to 0.3W (Idle) 6.5W(Active)	Up to 0.3W (Idle) 6.5W(Active)
Power Supply	3.3V DC				
Form Factor	M.2 (2280)				
Dimensions	3.8x80x22mm				
Weight			7g		
Operating Temperature	0°C-70°C				
Non-Operating Temp.	-40°C-85°C				
MTBF	1,500,000 hours				
TBW	350TB	600TB	1300TB	900TB	1800TB
Shock Resistant	1500G				
Data Correction	Built-in LDPC ECC provides the most-powerful data correction level in use today				
Warranty	7-year warranty				





IGB = 1,000,000,000 bytes, 1MB = 1,000,000 bytes Specifications are subject to change without notice







www.titaniummicro.com